

ThruWall Depositories

Product: KwikDrop Single ThruWall

Catalog#: 10-8951

Specifications are subject to change without notice. Please see www.kingsley.com for the most current specifications. **Made in the USA.**

ThruWall System Construction/Features

Materials:	<ul style="list-style-type: none">• Exterior: Heavy-duty stainless steel faceplate, depository door flap, and built-in weather hood.• Interior: Stainless steel throughout to include 14-inch four-sided chute housing. AirBloc neoprene rubber panels.
Weather Resistance:	Angled built-in weather hood shields from rain and snow. The spring-loaded depository door will not blow open in most winds. Caulking on the inside edges of the faceplate and weather stripping around door create increased protection from inclement weather.
Air Draft Prevention:	The AirBloc system helps to eliminate drafts caused when the depository door is opened.
Theft Deterrence:	The upward angle of external shroud, length of the internal slide chute, and the AirBloc system prevent reaching inside through the depository door and block theft of materials with a claw apparatus. The angle of the external shroud also acts as a deterrent to pouring liquids into the unit.
Available Wording:	Self-adhesive vinyl decal. See website for complete list of available wording options.
Locking Method:	Easy to operate KwikLock System allows locking the depository door with a simple "Open/Close" Lever. Note: KwikLock system is an integral part of the unit and is <u>not</u> available separately.
ADA Compliance:	ADA compliant when properly installed.
Assembly Required:	The KwikDrop ThruWall unit comes in two pieces: faceplate with slide and chute housing. This allows the faceplate to be smaller but makes wall installation more challenging. KwikLock system also requires assembly.
Compatibility:	Compatible with any Kingsley high capacity receiving cart.

ThruWall Measurements

Overall Dimensions:	20" W x 17 ^{-3/16} " D x 18 ^{-3/16} " H [508 mm W x 436.6 mm D x 461.9 mm H]
External Faceplate:	20" W x 12 ^{-3/4} " D x 13" H [508 mm W x 324 mm D x 330 mm H] (from front of shroud to end of entry chute)
Interior Chute Assembly:	15 ^{-3/4} " W x 14" D x 16 ^{-23/32} " H [400 mm W x 355.6mm D x 424.6 mm H]
Depository Opening:	15 ^{-1/8} " W x 3 ^{-7/8} " H [384.2 mm W x 98.4 mm H]
Product Weight:	19 lbs. [7.71 kg]
Shipping Method/Class:	Ground or freight/class 150

Installation

(Rough cut only. Please visit www.kingsley.com for complete instructions)

Rough Cut:	18 ^{-1/4} " W x 11 ^{1/4} " H [464 mm W x 286 mm H]. 40 ^{-3/4} " [1035.1 mm] max from external floor to bottom of rough cut opening.
Trim:	Keep 3" [76.2mm] horizontal from front to back then angle 90 degrees downward 7" [177.8mm] and continue horizontally through back of wall. Sides and bottom of opening trimmed with 3/4" thick wood. This trim is for the installing mounting hardware

Accessories/Options for This System:

Braille Tags – Reads: BOOK DROP (#99-8100) or VIDEO DROP (#99-8105)

Custom Wording – Call for quote.

DISCLAIMER: Lightweight material such as thin books or jewel cases may have difficulty passing through the AirBloc system.