



Product: Through Wall Envelope depository
Catalog #: 12-8100

Date of Revision: August 11, 2015. Go to www.kingsley.com for all updates.
Specifications are subject to change without notice. **MADE IN THE USA**

INCLUDED WITH THIS SYSTEM:

A complete easy to install through wall system with state of the art features. The system includes the faceplate with Kwik Drop depository, attached chute housing with interior locking door system; plus all features listed below. The design allows it to be installed in walls up to 13 inches thick.

ACCESSORIES FOR THIS SYSTEM

N/A

THROUGH WALL EXTERIOR CONSTRUCTION/FEATURES

Construction Materials:	16-gauge stainless steel exterior faceplate and depository door. With Graffiti-X clear coat. Locking rear door is coated with a primer allowing the ability to paint the interior side to match the building interior.
--------------------------------	--

Construction Methods:	The depository door is mounted into a built in weather hood and opens upward. It is also gravity and weight balanced allowing it to automatically close after materials have passed through. All edges are honed smooth.
------------------------------	--

THROUGH WALL INTERIOR CONSTRUCTION/FEATURES

Construction Materials:	Chute Housing: .040 inch aluminum housing. Faceplate: .063 inch Stainless Steel and angled upwards. All edges are honed smooth.
--------------------------------	---

Construction Methods:	The chute housing has four sides, extends 13 inches from the faceplate and will cover the wall rough cuts when installed. Interior locking door system is located at the rear of the unit, keeping contents contained.
------------------------------	---

SYSTEM FEATURES

Weather Resistance:	Weather hood with gravity, weight balanced and weather sealed depository flap helps to prevent the entry of rain and snow. Will not blow open in most winds. Weather stripping on the inside edges of the faceplate provide further protection from inclement weather.
----------------------------	---

Theft Deterrence:	Weather hood, flap and narrow entry slot all together make the theft deterrent system.
--------------------------	--

Locking Method:	High security cam lock that locks the door on the inside of the building creating a secured contained system.
------------------------	---

ADA Compliancy:	ADA compliant when properly installed
------------------------	---------------------------------------

Available wording: Self-adhesive decal in black that reads: PAYMENT, KEY DROP, NIGHT DROP.
Peel-off easy to mount decal in black.

Overall Dimensions: 22"L x 17-1/2" W x 20"H [558.8mmW x 444.5mmD x 508.0mmH]

Depository opening: 13 7/16"W x 5/8"H [341.31mmW x 15.87mmH]

Product Weight: 22 lbs [9.88 kg]

Shipping Method/Class: Ships assembled Ground or LTL/Class 150

INSTALLATION (Rough cut only; please visit www.kingsley.com for complete instructions)

Rough Cut dimensions and trim 36-1/2" [927.1mm] from exterior floor to bottom of cut out.
Rough cut opening 20-3/16"W x 18-5/16"H [512.76mmW x 465.1mmH] all the way through wall.
1/4" [6.35mm] trim on the top, bottom and sides of opening.
