



duraLight™ Cart

Product: 60 Series duraLight™ easyRoller™ safeGuard™ Cart

Catalog#: 30-9660

Specifications are subject to change without notice. Please see www.kingsley.com for the most current specifications. **Made in the USA.**

duraLight™ Cart Construction/Features

Materials:	16 gauge aircraft grade aluminum body for strength and all-weather use. Durable felt padding at the bottom of the float tray to protect collection from damage. An aluminum lid folds up and over to help keep rain out and locks in place with a cam lock.
Casters:	5" diameter corner mount casters; two swivel(locking) and two rigid. Caster wheels are non-marring, plate mounted, with ball bearings for smooth rolling operation. The larger casters help provide better mobility over thresholds and plush carpet.
Ergonomics:	Designed to help reduce and prevent strain on the back and shoulders. Float tray lowers as materials are received and raises as materials are removed. The cart height is designed to be pushed in an ergonomic manner for the average person.
Finish:	Corrosion resistant aluminum with a line grain finish.
Assembly Required:	Caster assembly required.
Capacity:	17.5 cubic feet, 600 lbs. weight capacity.
Versatility:	Can be used with most conveyor systems.



Cart Measurements

Overall Dimensions: 31.13" W x 32.39" D x 39.18" H
[791 mm W x 823 mm D x 995 mm H]
Height includes casters and depth includes handle.

Product Weight: 41 lbs.

Shipping Method/Class: Freight/class 150

Matching Depositories:

Compatible with all Kingsley 50 and 70 outdoor and indoor depositories.

Accessories/Options for this Cart:

Cart cover - #39-2005

Lightweight Springs - #99-3031

Standard Springs - #99-3022

Casters - #99-3006

Bottom Pad - #99-2532